

Lovejoy flexible couplings and power transmission products address critical operational issues that occur in marine material handling facilities. We provide solutions that are resistant to corrosion, require no lubrication, lower maintenance and downtime costs, and reduce noise levels – all with the level of quality, value, and customer service you expect from Lovejoy.

COMMON APPLICATIONS

Hoists and Cranes	Conveyors
Propulsor and Thruster	Aux Engines and Generators
Pumps	Winches and Windlass
HVAC Systems	
Fork Lifts	

Grid Couplings

- Horizontal and vertical split cover designs
- Interchangeable with industry standards up to size 1200
- Available in 19 sizes with a maximum bore of 13" and a maximum torque of 1,650,000 in-lbs
- Provides torsional damping
- Drop-out spacers for pump systems



HercuFlex® Gear Couplings

- Bore sizes from 7/16" to 42"
- Special styles available including spacer, floating shaft, and stainless steel
- Interchangeable with industry standards
- Torque capacity to 47,000,000 in-lbs
- Vari-Crown® teeth increase coupling wear life
- High performance gear for extreme high speed applications, offering a reduced moment of inertia




Torsional Couplings

- Maintenance free coupling solutions for any drive train involving diesel power or other sources of torsional excitation



QUICK FLEX® Couplings

- Transmit the same or higher torque than a gear, grid, chain or elastomeric coupling with similar dimensions
- Easy to install and requires no lubrication
- Replace insert without moving hubs



S-Flex Endurance™

- Elastomer-in-shear design
- Torque capacity up to 72,480 in-lbs
- Maximum bore of 5-1/2"
- Three sleeve materials provide flexibility in adapting to application requirements
- Fully interchangeable with industry standards
- Wide selection of both inch and metric finished bores



Disc Couplings

- No need for lubrication
- Ability to inspect without disassembly
- Torsionally rigid without any backlash
- No wearing parts
- High resistance to harsh environments
- Bore range to 15.25 inches
- 3,309,000 in-lbs of maximum torque
- Meets API 610, 671 standards
- Special styles available such as close coupled, spacer, drop out and adjustable shaft



RunRight® Motor Bases

- Maintenance free tensioning provides constant torque and less energy consumption
- Design compensates for startup belt load, absorbs load impact during operation while providing stability for proper alignment
- Increases life of the drive system
- Greatly simplifies belt changes, reducing costs for labor and downtime



RunRight® Tensioners

- Self-adjusting/tensioning
- Extends belt life
- Eliminates scheduled belt tensioning maintenance
- Stainless Steel complies with DIN 1.4301 and AISI 304 specifications



Ultra Temp Coupling Spiders

- Larger continuous temperature range and higher nominal & max torque
- 10% increase in radial misalignment, superior hydrolysis and best in class dampening

