# Timken Safety End Caps

## Timken Safety End Caps make workplace protection a snap.

- Helps protect workers
- Meets OSHA requirements
- Retrofit kit design
- Extends bearing life

Easy-to-install Timken Safety End Caps protect exposed rotating shafts, reducing hazards around many types of equipment. The patent-pending design meets all applicable OSHA requirements.

The new Fafnir safety product line consists of a mounting ring and snapon cover, both molded in a durable, bright yellow polymer. The end cap snaps into the adhesive-backed ring that adheres to the outboard face of most flanged bearing housings. The secure, 360° fit makes for a rugged unit that also provides basic protection from contaminants and washdown.

Factory retrofits are a snap with everything provided in a handy kit. The cost-effective end covers are simple to install on Timken and most other flanged units. Current sizes range from

<sup>3</sup>/<sub>4</sub>-inch to 1-<sup>15</sup>/<sub>16</sub>-inch (20mm to 50mm) shaft sizes for two or four-bolt flanged cast iron, malleable iron, and other selected housing styles and sizes.

# TIMKEN

#### **Safety End Cap Benefits**

**Improved safety** – convenient means to protect factory workers from contact with rotating stub shafts.

**OSHA requirements** – design meets current OSHA regulations mandating safety covers for exposed shafting.

**Easy installation** – end cap snaps easily and securely into adhesive-backed mounting ring.

**High visibility** – both end cap and mounting ring are molded in bright yellow for optimum visibility and safety.

Simple retrofit – convenient field installation involves easy attachment of mounting ring to outboard face of a variety of housed units from different manufacturers.

Flexible use – easy field installation expands application for housed units produced by a variety of manufacturers.

**Cost efficiency** – quick and simple field retrofits minimize downtime and avoid replacing existing housed units.

**Durable service** – tough polymer components and strong adhesive bond stand up to typical factory usage.

**Contamination protection** – end cap with 360° interlocking fit provides basic protection against contamination and washdown.

**Convenient kits** – everything needed for installation is provided in a handy kit.

# Applications Material Handling

- Conveyors
- Packaging Lines
- Luggage Handling

**Food Processing** 



#### Design

Timken Safety End Caps install securely into an adhesive-backed mounting ring with a 360° interlocking fit. The 3M VBH high-performance, pressure-sensitive adhesive maintains a stable and durable contact on outboard face surfaces of popular housed units. 3M rates this adhesive from -20°F to nearly 300°F (for short periods of time). Caps offer excellent solvent and UV resistance, as well as protection against contamination and washdown.

#### **Kit Contents**

Timken Safety End Caps come in a convenient kit that contains everything required for a safe and durable mounting:

- Polymer end cap
- Adhesive-backed polymer mounting ring
- · Scuffing pad
- Cleaning cloth

#### Installation

Main steps in the simple mounting procedure include:

- Use the scuffing pad on housing's mating surface where the mounting ring will be placed.
- 2. Clean off mounting area.
- 3. Attach adhesive-backed mounting ring.
- 4. Hold mounting ring in place with pressure for 60 seconds.
- 5. Allow adhesive to set for minimum of one hour.
- 6. Snap end cap into place.

For your nearest Timken sales representative, call (800) 223-1954. Outside the U.S. and Canada, call (330) 438-3000.



Timken Safety End Caps protect against rotating stub shafts.



Kit contains everything needed for durable mounting.



Simple mounting procedures enhance end cap value.

#### **Ordering Information**

KIT *	SHAFT SIZES
204 ECY KIT	¾, 20mm
205 ECY KIT	<sup>7</sup> / <sub>8</sub> , <sup>15</sup> / <sub>16</sub> , 1, 25mm
206 ECY KIT	1½,6, 1½, 1¾5, 30mm
207 ECY KIT	1¼, 1 <sup>5</sup> / <sub>16</sub> , 1 <sup>3</sup> / <sub>8</sub> , 1 <sup>7</sup> / <sub>16</sub> , 35mm
208 ECY KIT	1½, 40mm
209 ECY KIT	15/8, 111/ <sub>16</sub> , 13/4, 45mm
210 ECY KIT	1 <sup>15</sup> ⁄ <sub>16</sub> , 2S, 50mm

\*Kits are designed to fit the following Timken Fafnir® housed units:

4-Bolt: YCJ, RCJ, RCJC, TCJ, LCJ, SCJ, VCJ

2-Bolt: YCJT, RCJT, RCJTC, TCJT, LCJT, SCJT, VCJT

### TIMKEN

The Timken team applies their know-how to improve the reliability and performance of machinery in diverse markets worldwide. The company designs, makes and markets high-performance mechanical components, including bearings, gears, belts, chain and related mechanical power transmission products and services.