

# **SAFETY DATA SHEET**

#### 1. Identification

Product name TIMKEN GR180

Other means of identification No data available.

Recommended use: Lubricating grease

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

**Distributor** 

Company Name: The Timken Corporation Address: 4500 Mt. Pleasant St. NW

North Canton, OH 44720 USA

Telephone: 234.262.3000

Emergency telephone number: INFOTRAC US & CANADA - 800.535.5053 Outside U.S. & Canada

+1 352.323.3500

# 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Skin sensitizer Category 1
Toxic to reproduction Category 2

# **Label Elements**

# **Hazard Symbol:**



Signal Word: Warning

**Hazard Statement:** May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Precautionary Statements

SDS\_US 1/9



**Prevention:** Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Avoid breathing

dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

**Response:** IF ON SKIN: Wash with plenty of soap and water. Wash contaminated

clothing before reuse. If skin irritation or rash occurs: Get medical

advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

**Disposal:** Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Other hazards which do not result in GHS classification:

None.

#### **Unknown toxicity - Health**

Acute toxicity, oral 21.43 %
Acute toxicity, dermal 14.62 %
Acute toxicity, inhalation, vapor 42 %
Acute toxicity, inhalation, dust 41.8 %

or mist

#### 3. Composition/information on ingredients

# **Hazardous Component(s):**

Chemical name	CAS-No.	Concentration
Residual oils	Confidential	30 - <60%
Polymer	Confidential	1 - <10%
Mineral oil	Confidential	1 - <10%
Dodecylbenzene calcium sulfonate	Confidential	1 - <10%
Calcium carbonate	471-34-1	1 - <5%
Calcium 12-hydroxyoctadecanoate	Confidential	1 - <5%
Naphthenic acids, zinc salts	Confidential	1 - <5%
Magnesium silicate	14807-96-6	1 - <5%
Benzenamine, N-phenyl-, reaction products with	68411-46-1	0.1 - <1%
2,4,4-trimethylpentene		

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

# 4. First-aid measures

Ingestion: Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

**Inhalation:** Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

SDS\_US 2/9



**Eye contact:** Flush thoroughly with water. If irritation occurs, get medical assistance.

Continue to rinse for at least 15 minutes.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

**Environmental Precautions:** 

Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

SDS\_US 3/9



# 7. Handling and storage

**Precautions for safe handling:** Observe good industrial hygiene practices. Wear appropriate personal

protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after

handling.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

# 8. Exposure controls/personal protection

# **Exposure Limits**

Chemical name	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesium silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Magnesium silicate	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

**Protective Measures:** Use personal protective equipment as required.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

# 9. Physical and chemical properties

SDS\_US 4/9



**Appearance** 

Physical state: solid
Form: Grease
Color: Amber
Odor: Mild

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:250 °C (482 °F)Evaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

Relative density: 0.95

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

# 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

Hazardous Decomposition Thermal decomposition or combustion may liberate carbon oxides and

**Products:** other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

SDS\_US 5/9



**Inhalation:** None under normal conditions. This product contains a low concentration of

hydrated magnesium silicate (Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix (grease). As a consequence, exposure to

airborne Talc particles/dusts is not anticipated.

**Skin Contact:** May cause an allergic skin reaction.

**Eye contact:** Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): > 5000 mg/kg

**Dermal** 

**Product:** ATEmix (): 2000 - 5000 mg/kg

Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

**Serious Eye Damage/Eye Irritation** 

**Product:** No data available.

Respiratory or Skin Sensitization

**Product:** May cause an allergic skin reaction.

Carcinogenicity

SDS\_US 6/9



**Product:** This product contains a low concentration of hydrated magnesium silicate

(Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix

(grease). As a consequence, exposure to airborne Talc particles/dusts is not

anticipated.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Magnesium silicate Overall evaluation: 1. Carcinogenic to humans.

# **US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

**Product:** No data available.

Specific Target Organ Toxicity - Repeated Exposure

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

# 12. Ecological information

**General information:** This product has not been evaluated for ecological toxicity or other

environmental effects.

# 13. Disposal considerations

SDS US 7/9



**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

# 14. Transport information

DOT

Not regulated.

**IMDG** 

Not regulated.

**IATA** 

Not regulated.

# 15. Regulatory information

# **US Federal Regulations**

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

kidney effects Crystalline silica

lung effects

immune system effects

Cancer

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Respiratory or Skin Sensitization Reproductive toxicity

SARA 313 (TRI Reporting)

Reporting Reporting threshold for threshold for manufacturing and other users processing

**Chemical Identity** Naphthenic acids, zinc

salts

10000 lbs 25000 lbs.

#### **US State Regulations**

SDS\_US 8/9



# **US. California Proposition 65**



This product can expose you to chemicals including Magnesium silicate Crystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

# 16.Other information, including date of preparation or last revision

**Issue Date:** 22.02.2023

**Revision Date:** 24.01.2023

Version #: 1.0

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS\_US 9/9