

SAFETY DATA SHEET

1. Identification

Product name	TIMKEN GR181
Other means of identification	No data available.
Recommended use:	Lubricating grease
Restrictions on use:	Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Distributor	
Company Name:	The Timken Corporation
Address:	4500 Mt. Pleasant St. NW
	North Canton, OH 44720 U.S.A.
Telephone:	234.262.3000

Emergency telephone number: INFOTRAC US & CANADA - 800.535.5053 Outside U.S. & Canada +1 352.323.3500

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation	Category 2
Skin sensitizer	Category 1
Toxic to reproduction	Category 2

Label Elements

Hazard Symbol:



Signal Word:	Warning
Hazard Statement:	Causes skin irritation. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child.



Precautionary Statements	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.
Response:	IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing. Specific treatment (see supplemental first aid instructions on this label). IF exposed or concerned: Get medical advice/attention.
Storage:	Store locked up.
Disposal:	Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards which do not	None.
result in GHS classification:	

Unknown toxicity - Health	
Acute toxicity, oral	24.35 %
Acute toxicity, dermal	19.96 %
Acute toxicity, inhalation, vapor	49.25 %
Acute toxicity, inhalation, dust or mist	49.05 %

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Residual oils	Confidential	30 - <60%
Mineral oil	Confidential	1 - <10%
Dodecylbenzene calcium sulfonate	Confidential	1 - <10%
Polymer	Confidential	1 - <10%
Calcium carbonate	471-34-1	1 - <10%
Calcium 12-hydroxyoctadecanoate	Confidential	1 - <5%
Naphthenic acids, zinc salts	Confidential	1 - <5%
Magnesium silicate	14807-96-6	1 - <5%
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	0.1 - <1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures

Ingestion:

Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.



Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.	
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Most important symptoms/effects	s, acute and delayed	
Symptoms:	No data available.	
Indication of immediate medical at	tention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) extingu	ishing media	
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment and	I precautions for fire-fighters	
Special fire-fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures	;	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.	
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.	
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.	



7. Handling and storage

Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash hands thoroughly after handling. Avoid contact with eyes, skin, and clothing.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesium silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Magnesium silicate	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

Protective Measures:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance **Physical state:** solid Semisolid Form: Color: Amber Odor: Mild Odor threshold: No data available. pH: No data available. Melting point/freezing point: No data available. Initial boiling point and boiling range: No data available. Flash Point: 250 °C (482 °F) **Evaporation rate:** No data available. Flammability (solid, gas): No data available. Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): No data available. Flammability limit - lower (%): No data available. **Explosive limit - upper:** No data available. **Explosive limit - lower:** No data available. No data available. Vapor pressure: No data available. Vapor density: 0.95 **Relative density:** Solubility(ies) Solubility in water: Insoluble in water Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. No data available. Auto-ignition temperature: **Decomposition temperature:** No data available. Viscosity: No data available.

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



Information on likely routes of exposure

11. Toxicological information

Ingestion:May be harmful if swallowed.Inhalation:None under normal conditions. This product contains a low concentration of
hydrated magnesium silicate (Talc). Under the International Agency for
Research on Cancer (IARC), Talc in powder form is classified as Group 1:
Carcinogenic to Humans. This is based on exposure through inhalation and
perineal dusting with talc-based body powders. For this product, Talc is
bound in the product's matrix (grease). As a consequence, exposure to
airborne Talc particles/dusts is not anticipated.Skin Contact:Causes skin irritation. May cause an allergic skin reaction.Eye contact:Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics Ingestion: No data available.

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix (): > 5000 mg/kg
Dermal Product:	ATEmix (): 2000 - 5000 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritation Product:	on No data available.
Respiratory or Skin Sensitization Product:	n May cause an allergic skin reaction.

Carcinogenicity



Product:	This product contains a low concentration of hydrated magnesium silicate (Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix (grease). As a consequence, exposure to airborne Talc particles/dusts is not anticipated.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Magnesium silicate Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended: No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity Product:	- Single Exposure No data available.
Specific Target Organ Toxicity Product:	- Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.
12. Ecological information	
General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
12 Dispession considerations	

13. Disposal considerations



Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

ΙΑΤΑ

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities. Crystalline silica kidney effects lung effects immune system effects Cancer

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Skin Corrosion or Irritation Respiratory or Skin Sensitization Reproductive toxicity

SARA 313 (TRI Reporting)

	<u>Reporting</u> threshold for	Reporting threshold for	
		manufacturing and	
Chemical Identity	other users	processing	
Naphthenic acids, zinc	10000 lbs	25000 lbs.	
salts			

US State Regulations



US. California Proposition 65



This product can expose you to chemicals includingMagnesium silicateCrystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision	
Issue Date:	22.02.2023
Revision Date:	26.01.2023
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.